

OCTG - Seamless Steel Line Pipe

Product Characteristics:

Certified API products with API monogram
 Non Upset and External Upset End finish
 Standard and exact lengths
 Plain end or threaded and coupled
 Quench and temper

Specifications:

API 5 CT
 PSL-1, PSL-2

Grades:

All grades up-to X-70

Size Range (indicated in blue):



OD/ wall																		
0.840	0.110	0.150																
1.050	0.110	0.150																
1.320		0.130	0.180															
1.660		0.140	0.190															
1.900		0.150	0.200															
2.375	0.110	0.130	0.140	0.150	0.170	0.190	0.220	0.250	0.280									
2.875	0.110	0.130	0.140	0.160	0.170	0.190	0.220	0.250	0.280									
3.500	0.110	0.130	0.140	0.160	0.170	0.190	0.220	0.250	0.280	0.300								
4.000	0.110	0.130	0.140	0.160	0.170	0.190	0.220	0.250	0.280	0.320								
4.500		0.130	0.140	0.160	0.170	0.190	0.220	0.250	0.280	0.310	0.530							
5.563		0.130	0.140	0.160	0.170	0.190	0.220	0.250	0.280	0.310	0.530							
6.625		0.250	0.280	0.312	0.344	0.375	0.432	0.500	0.562	0.625	0.719	0.750	0.864	0.875				
8.625		0.250	0.277	0.312	0.322	0.375	0.438	0.500	0.562	0.625	0.719	0.750	0.812	0.875	1.000			
10.750		0.250	0.279	0.307	0.344	0.365	0.438	0.500	0.562	0.625	0.719	0.812	0.875	0.938	1.000			
12.750		0.330	0.344	0.375	0.438	0.500	0.562	0.625	0.688	0.750	0.812	0.875	0.938	1.000	1.062	1.125	1.250	
14.000			0.344	0.375	0.438	0.500	0.562	0.625	0.688	0.750	0.812	0.875	0.938	1.000	1.062	1.125	1.250	

For Products, Sizes and Grades Not Listed — Please Inquire