

Tube- Seamless Aluminum

Product Characteristics:

- Dimensional accuracy
- Uniform mechanical properties
- Fine metallic structure
- Seamless and port hole extruded

Specifications:

- ASTM B 210
- ASTM B 241

Grades:

- 6061, 6063, 7000 series

Size Range (indicated in blue):



ASTM B-210

| WT(inch)/ OD(inch) | 0.035 | 0.049 | 0.065 | 0.083 | 0.095 | 0.109 | 0.120 | 0.125 |
|-----------------------|-------|-------|-------|-------|-------|-------|-------|-------|
| 0.250 | | | | | | | | |
| 0.313 | | | | | | | | |
| 0.375 | | | | | | | | |
| 0.500 | | | | | | | | |
| 0.625 | | | | | | | | |
| 0.750 | | | | | | | | |
| 0.875 | | | | | | | | |
| 1.000 | | | | | | | | |
| 1.125 | | | | | | | | |
| 1.250 | | | | | | | | |
| 1.500 | | | | | | | | |
| 1.750 | | | | | | | | |
| 2.000 | | | | | | | | |
| 2.250 | | | | | | | | |
| 3.000 | | | | | | | | |
| 3.500 | | | | | | | | |
| 4.000 | | | | | | | | |

ASTM B-241

| NPS/ Schedule | 1/4" | 3/8" | 1/2" | 3/4" | 1" | 1- 1/4" | 1- 1/2" | 2" | 2- 1/2" | 3" | 3- 1/2" | 4" | 5" | 6" | 8" | 10" | 12" |
|------------------|------|------|------|------|----|------------|------------|----|------------|----|------------|----|----|----|----|-----|-----|
| 10 | | | | | | | | | | | | | | | | | |
| 20 | | | | | | | | | | | | | | | | | |
| 40 | | | | | | | | | | | | | | | | | |
| 80 | | | | | | | | | | | | | | | | | |

For Products, Sizes and Grades Not Listed — Please Inquire